



# VT-49104 100W SMD FLOODLIGHT F-CLASS 4000K WHITE BODY



## FEATURES

- High quality LED SMD chip and high power driver
- Comparing with traditional halogen floodlights it can save upto 80% Energy
- Constant current Integrated IC driver - Built in driver - no external power supply required
- Built Strong and durable with Aluminium - Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.

## TECHNICAL INFORMATION

<b>Dimmable:</b>	No
<b>Color Temperature:</b>	4000K
<b>Model:</b>	VT-49104-W
<b>Watts:</b>	100
<b>Lumens:</b>	8700
<b>Input Power:</b>	AC:220-240V, 50/60Hz
<b>Unit Color:</b>	White
<b>Color for Web:</b>	Day White
<b>Body Type:</b>	Aluminium
<b>Dimension:</b>	270x27x222mm
<b>Operation Temperature:</b>	-20°C to +40°C
<b>Instant Start:</b>	0-100% in < 1s
<b>On/Off Cycles:</b>	>15000
<b>PF:</b>	>0.9
<b>LED Chip Type:</b>	SMD
<b>Beam Angle:</b>	110°
<b>CRI:</b>	>70
<b>Downward LOR (%):</b>	100
<b>Upward LOR (%):</b>	0
<b>Energy Rating Label:</b>	F (2021)
<b>IP Rating:</b>	IP65
<b>Long Life:</b>	25,000 Hours
<b>Energy Saving:</b>	80 Energy



**IP65**  
STANDARD

**02**  
YEAR  
WARRANTY

## LISTING DETAILS

<b>SKU:</b>	6725
<b>Model:</b>	VT-49104-W
<b>EAN:</b>	3800157684361
<b>Commodity Code:</b>	94054210

## PACKAGING

<b>Gross Weight (Kgs):</b>	1.26
<b>Unit CBM:</b>	0.002426
<b>Dimension:</b>	270x27x222mm

## MASTER BOX PACKAGING

<b>Box Qty:</b>	10
<b>Qty Per Pallet:</b>	500
<b>Length (Box) mm:</b>	275
<b>Width (Box) mm:</b>	30
<b>Height (Box) mm:</b>	225