





TECHNICAL INFORMATION

Watts:	100	
Lumens:	16000	
Input Power:	AC:220-240V, 50Hz	
Long Life:	30,000 Hours	
Unit Color:	Black	
Body Type:	Die Cast Aluminium	
PF:	>0.9	
LED Chip Type:	SMD	
CRI:	>70	
Operation Temperature:	-20°C to +45°C	
Dimmable:	No	
Beam Angle:	100°	
Color:	4000K	
Dimension:	247.5x49.5x299mm	
lumens per watt:	160	

IP65 RATING S YEAR

FEATURES

- Perfect replacement for Metal Halide Floodlights, High Pressure Sodium Floodlights and Halogen Floodlights
- Product designed with high lumen efficiency of 160 LM/W
- High quality LED SMD chip and high power driver
- Fascia glass sealed with Silicone Rubber for superior waterproof /airtight performance
- Constant current Integrated IC driver Built in driver no external power supply required
- Built Strong and durable with Die Cast Aluminium Corrosion resistant design
- Suitable for building facades, sports facilities, industrial, commercial billboards, hoardings, parking lots etc.
- Recommended daily usage: 10 12 hours *Exceeding recommended daily usage will void warrantyy

160LM SLIMLINE SERIES | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 5920 - 934 938 View more details



PACKAGING

Gross Weight: 1.98 Unit CBM: 0.005446 Dimension: 247.5x49.5x299mm

MASTER BOX PACKAGING

Box Qty: 4

LISTING DETAILS

Commodity Code: 9405403990 EanCode: 3800157654722



www.vtacexports.com