





TECHNICAL INFORMATION

Lumens:	4200	
Input Power:	DC:10V	
Long Life:	20,000 Hours	
Unit Color:	Black	
Body Type:	ABS+PC+Glass	
LED Chip Type:	SMD	
Operation Temperature:	-20°C to +45°C	
Dimmable:	No	
Color Temperature:	6000K	
Dimension:	437x90x356mm	
Battery Type:	25000mAh	
Charging Time:	4 Hours	
Working Time:	8 Hours	
Solar Panel:	50W	

IP65

FEATURES

- Solar Powered Floodlight Zero electricity cost.
- Designed with Remote control, Auto and timer function.
- Flexible installation, designed with solar panel with 5 meter wire length
- Perfectly built for outdoor with Ingress protection of IP65
- $^{\circ}\,$ Suitable for Pathways, Garden, Patio and similar outdoor environment

CE/EMC CE/LVD



SOLAR FLOODLIGHTS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 94027 - 938 View more details



PACKAGING

Gross Weight (Kgs):	8.314
Unit CBM:	0.03672
Dimension:	437x90x356mm

MASTER BOX PACKAGING

Box Qty:2Qty Per Pallet:32Length (Box) mm:120Width (Box) mm:450Height (Box) mm:680

LISTING DETAILS

Ean Code: 3800157645799