



## TECHNICAL INFORMATION

Watts:	40
Lumens:	4000
Shape:	Rectangle
Input Power:	AC:200-240V,50/60Hz
Long Life:	20,000 Hours
Unit Color:	White
Body Type:	FE + PP
PF:	>0.9
LED Chip Type:	SMD
CRI:	>80
Operation Temperature:	-20°C to +40°C
Dimmable:	No
Beam Angle:	120°
Color Temperature:	4000K
Dimension:	1195x295x29mm
Output Voltage:	DC:410-453V



## FEATURES

- 2in1 Recessed and Surfaced installation
- Powerful LED light source with lumen efficiency of 100LM/W
- Strong and sturdy FE + PP Body
- Easy to Install and No UV radiation
- High quality power driver
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, hospitals etc



## 120X30 PANELS

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

*One brand, endless solutions..*

SKU: 6625 - 1410 940

[View more details](#)



No UV Radiation

## PACKAGING

Gross Weight (Kgs): 2.68

Unit CBM: 0.018469

Dimension: 1195x295x29mm

## MASTER BOX PACKAGING

Box Qty: 6

## LISTING DETAILS

Ean Code: 3800157662024