





TECHNICAL INFORMATION

Watts:	40
Lumens:	4000
Shape:	Square
Input Power:	AC:200-240V, 50/60Hz
Long Life:	20,000 Hours
Body Type:	FE + PP
PF:	>0.9
LED Chip Type:	SMD
CRI:	>80
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	120°
Color Temperature:	4000K
Dimension:	595x595x29mm
Output Voltage:	DC:410-453V
Input Current:	0.22A







📢 CRI>80

FEATURES

- Powerful LED light source with lumen efficeincy of 100 LM/W LM/W
- $^{\bullet}\,$ Fitted with high efficiency SMD LED Chips that offer up to 80% in energy savings

80%

- Featuring 2IN1 installation allowing flexible Recessed/surface installation
- Strong and sturdy FE + PP body
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.



2 IN 1 PANELS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions.

SKU: 6451 - 1410 View more details



PACKAGING

Gross Weight (Kgs):	14
Unit CBM:	0.0961
Dimension:	595x595x29mm

MASTER BOX PACKAGING

Box Qty:	1
Qty Per Pallet:	12
Length (Box) mm:	250
Width (Box) mm:	620
Height (Box) mm:	620

LISTING DETAILS

Commodity Code: 9405109890 Ean Code: 3800157636421