





TECHNICAL INFORMATION

Watts:	100
Lumens:	10000
Input Power:	AC:220-240V, 50Hz
Long Life:	25,000 Hours
Unit Color:	Black
Body Type:	Diecast Aluminium
PF:	>0.9
LED Chip Type:	SMD-Samsung Chip
CRI:	>80
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	100°
Color Temperature:	6500K
Dimension:	247.5x49.5x299mm
Sensor Type:	Light Sensor
lumens per watt:	100

• High quality Light Sensor Floodlight with a lumen output of 100LM/W

• When natural light is above 140Lux floodlight will be auto off and below

• Built Strong and durable with Die Cast Aluminium - Corrosion resistant

• Application - Facade lighting, lobby, garage, passage, parking lot and many



FEATURES

140Lux will be auto on



• Designed with high efficiency LED Samsung Chips

Light Sensor Floodlight donot detect any motion

• Light Sensor function with no turning on/off required

Perfectly built for outdoor with Ingress protection of IP65











Gross Weight (Kgs): 1.72 Unit CBM: 0.005443

247.5x49.5x299mm Dimension:

100

MASTER BOX PACKAGING

Box Qty: Length (Box) mm: 252 Width (Box) mm: 54 Height (Box) mm: 304

LISTING DETAILS

Ean Code: 3800157660457



LIGHT SENSOR PRO | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 20177 - 934 938 View more details





design

