





TECHNICAL INFORMATION

| Lumens: | 2300 | |
|--------------------|--------------|--|
| Body Type: | Aluminium | |
| LED Chip Type: | SMD | |
| Dimmable: | No | |
| Beam Angle: | 120° | |
| Color Temperature: | 6400K | |
| Dimension: | 680x320x50mm | |
| Output Voltage: | 3.2∨ | |
| Battery Type: | 30Ah | |
| Charging Time: | 4-6 Hours | |
| Working Time: | 8-10 Hours | |
| Solar Panel: | 33W | |



FEATURES

- Uses Solar Panel for efficient photovoltaic conversion and lengthy lifespan
- Remote Control with Radar Sensor and Auto and Timer function
- Easy Installation No Wiring
- 33W, 3.2V Polycrystalline Silicon Panel
- 1400lm in Auto on Mode & 2300lm in Sensor Mode
- Working time 8-10 Hours in always mode and 12 Hours in induction mode
- Zero electricity cost Solar Powered
- Suitable for Pathways, Garden, Patio and similar outdoor environment



LED LIGHTING | SOLAR STREETLIGHTS

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 6756 -View more details



PACKAGING

| Gross Weight (Kgs): | 6.17 |
|---------------------|--------------|
| Unit CBM: | 0.039333 |
| Dimension: | 680x320x50mm |

MASTER BOX PACKAGING

Box Qty:3Length (Box) mm:380Width (Box) mm:110Height (Box) mm:815

LISTING DETAILS

Commodity Code: 9405411000 Ean Code: 3800157686891