



### TECHNICAL INFORMATION

Lumens:	4300
Body Type:	Aluminium
LED Chip Type:	SMD
Dimmable:	No
Beam Angle:	120°
Color Temperature:	6400K
Dimension:	1000x320x50mm
Output Voltage:	3.2V
Battery Type:	60Ah
Charging Time:	4-6 Hours
Working Time:	8-10 Hours
Solar Panel:	50W

### SOLAR STREETLIGHTS | LED LIGHTING

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

### FEATURES

- Uses Solar Panel for efficient photovoltaic conversion and lengthy lifespan
- Remote Control with Radar Sensor and Auto and Timer function
- Easy Installation - No Wiring
- 50W, 3.2V Polycrystalline Silicon Panel
- 2200lm in Auto on Mode & 4300lm in Sensor Mode
- Working time 8-10 Hours in always mode and 12 Hours in induction mode
- Zero electricity cost - Solar Powered
- Suitable for Pathways, Garden, Patio and similar outdoor environment



### LISTING DETAILS

Ean Code: 3800157686938

### PACKAGING

Gross Weight (Kgs):	9.7
Unit CBM:	0.054733
Dimension:	1000x320x50mm

### MASTER BOX PACKAGING

Box Qty:	2
Qty Per Pallet:	24
Length (Box) mm:	380
Width (Box) mm:	110
Height (Box) mm:	1140