

Product Spec Sheet



VT-15200ST LED SOLAR STREETLIGHT 6500K 3.2V 50AH LIFePO4 BRIDGELUX CHIP IP65



FEATURES

- Solar Powered streetlight Zero electricity cost
- Designed with remote control and Lamp Post/Wall Mount 2IN1 installation
- Maximum Installation and Mounting Height 6-8 Meters
- Perfectly built for outdoor application with Ingress protection of IP65
- Includes Protruding Pole, Mounting Arm, Solar Panel, 1.5M
 Cable, Expansion Screws, Solar Panel Bracket, 1 Expansion
 Plate and Remote Control
- Suitable for Pathways, Garden, Patio and similar outdoor environment

TECHNICAL INFORMATION

Solar Panel:	OUVV
Color Temperature:	6500K
Model:	VT-15200ST
Lumens:	3000
Color for Web:	White
Dimension:	200x530mm
Working Time:	8-10 Hours
LED Chip Type:	SMD
Beam Angle:	120°
Battery Type:	Life PO4, 3.2V 50000mAh Battery
IP Rating:	IP65
Wire Length:	1.5m
Charging Time:	4-6 Hours

IP65 STANDARD



LISTING DETAILS

SKU:	10227
Model:	VT-15200ST
EAN:	3800170205970
Commodity Code:	94054110

PACKAGING

Gross Weight (Kgs):	10.7
Unit CBM:	0.083648
Dimension:	200x530mm

MASTER BOX PACKAGING

Box Qty:	1
Qty Per Pallet:	18
Length (Box) mm:	740
Width (Box) mm:	595
Height (Box) mm:	195