

Product Specification Sheet



Technical Information

Instant Start:	0-100% in	IP Rating:	IP65
Watts:	50	Dimmable:	No
Lumens:	6000	Warranty (Years):	5
On/Off Cycles::	>15000	PF:	>0.9
Beam Angle:	100	CRI:	>80
Unit Color:	Black	Operation Temperature:	-20°C to +45°C
Body Type:	Die Cast Aluminium	Input Power:	AC:220-240V,50Hz
Long life:	30,000 Hours	Sensor Compatibility:	Yes
LED Chip Type:	SMD		

Features

- Perfect replacement of Metal Hallide Floodlight, High Pressure Sodium Floodlight & Halogen Floodlight
 - Fascia glass sealed with SILICONE RUBBER ensuring superior waterproof /airtight performance
 - High Power LED Samsung Chip
 - Constant current Integrated IC driver
 - Premium Quality Die Casting Aluminium Body
 - **Corrosion Resistant**
 - Available in different color options of White , Day White & Warm White
 - Complies with LM-80
 - Excellent coverage for area and façade lighting
 - Application Building Façade, Sports Facilities, Industrial, Commercial Bill Boards & Hoardings, Parking Lots etc



Suitable & Recommended for maximum daily use of 10-12 hours, usage beyond this would void the warranty

Packaging

Unit Details		Listing Details				
Gross Weight(GW) Kgs	0.952265	EAN Code	3800157646260			
Unit CBM	0.00195	Commodity Code	9405403990			
Master Box Packaging						
Master Box Qty (Pcs Per Carton)	8					
READY STOCKS IN UK & EU WWW.vtacexports.com						